

Models DNC-T2003 through DNC-T2032

Notes:

1. Replacement models DNC-T20**-020 is mounted to a standard 6.75" x 4.75" mounting plate. Replacement modes DNC-T20**-R20 is attached to a retrofit mounting plate. See catalog page for dimensions.

OBSOLETE MODEL						REPLACEMENT MODEL					
Model #	Input Voltage	Max # of Outputs	Programmable number of Outputs	Programmable ON TIME in seconds	Programmable OFF TIME in seconds	Model # ¹	Input Voltage	Max # of Outputs	Programmable number of Outputs	Programmable ON TIME in seconds	Programmable OFF TIME in seconds
DNC-T2003-A10	120 VAC	3	1 - 3	.050 - .500	1.5 - 30	DNC-T2003-020	95 to 265 VAC	3	1-3	.050 - .600	1 - 999
DNC-T2003-B10	120 VAC	3	1 - 3	.050 - .500	8.5 - 180	DNC-T2003-020	95 to 265 VAC	3	1-3	.050 - .600	1 - 999
DNC-T2006-A10	120 VAC	6	2 - 6	.050 - .500	1.5 - 30	DNC-T2006-020 DNC-T2006-R20	95 to 265 VAC	6	1-6	.050 - .600	1 - 999
DNC-T2006-B10	120 VAC	6	2 - 6	.050 - .500	8.5 - 180	DNC-T2006-020 DNC-T2006-R20	95 to 265 VAC	6	1-6	.050 - .600	1 - 999
DNC-T2010-A10	120 VAC	10	3 - 10	.050 - .500	1.5 - 30	DNC-T2010-020 DNC-T2010-R20	95 to 265 VAC	10	1-10	.050 - .600	1 - 999
DNC-T2010-B10	120 VAC	10	3 - 10	.050 - .500	8.5 - 180	DNC-T2010-020 DNC-T2010-R20	95 to 265 VAC	10	1-10	.050 - .600	1 - 999
DNC-T2010-ADC	12 - 24 VDC	10	2 - 10	.050 - .500	1.5 - 60	DNC-T2010-BDC	12 - 24 VDC	10	1-10	.050 - .600	1 - 999
DNC-T2020-A10	120 VAC	20	11 - 20	.050 - .500	1.5 - 30	DNC-T2020-020 DNC-T2020-R20	95 to 265 VAC	20	1-20	.050 - .600	1 - 999
DNC-T2020-B10	120 VAC	20	11 - 20	.050 - .500	8.5 - 180	DNC-T2020-020 DNC-T2020-R20	95 to 265 VAC	20	1-20	.050 - .600	1 - 999
DNC-T2032-A10	120 VAC	32	17 - 32	.050 - .500	1.5 - 30	DNC-T2032-020 DNC-T2032-R20	95 to 265 VAC	32	1-32	.050 - .600	1 - 999
DNC-T2032-B10	120 VAC	32	17 - 32	.050 - .500	8.5 - 180	DNC-T2032-020 DNC-T2032-R20	95 to 265 VAC	32	1-32	.050 - .600	1 - 999
DNC-T2006-A220	220 VAC	6	2 - 6	.050 - .500	1.5 - 30	DNC-T2006-020 DNC-T2006-R20	95 to 265 VAC	6	1-6	.050 - .600	1 - 999
DNC-T2006-B220	220 VAC	6	2 - 6	.050 - .500	8.5 - 180	DNC-T2006-020 DNC-T2006-R20	95 to 265 VAC	6	1-6	.050 - .600	1 - 999
DNC-T2010-A220	220 VAC	10	3 - 10	.050 - .500	1.5 - 30	DNC-T2010-020 DNC-T2010-R20	95 to 265 VAC	10	1-10	.050 - .600	1 - 999
DNC-T2010-B220	220 VAC	10	3 - 10	.050 - .500	8.5 - 180	DNC-T2010-020 DNC-T2010-R20	95 to 265 VAC	10	1-10	.050 - .600	1 - 999
DNC-T2020-A220	220 VAC	20	11 - 20	.050 - .500	1.5 - 30	DNC-T2020-020 DNC-T2020-R20	95 to 265 VAC	20	1-20	.050 - .600	1 - 999
DNC-T2020-B220	220 VAC	20	11 - 20	.050 - .500	8.5 - 180	DNC-T2020-020 DNC-T2020-R20	95 to 265 VAC	20	1-20	.050 - .600	1 - 999
DNC-T2032-A220	220 VAC	32	17 - 32	.050 - .500	1.5 - 30	DNC-T2032-020 DNC-T2032-R20	95 to 265 VAC	32	1-32	.050 - .600	1 - 999
DNC-T2032-B220	220 VAC	32	17 - 32	.050 - .500	8.5 - 180	DNC-T2032-020 DNC-T2032-R20	95 to 265 VAC	32	1-32	.050 - .600	1 - 999